

**Chiller, air source for outdoor installation  
43,9-129 kW**

Outdoor unit for the production of chilled water with fixed speed and variable speed (Inverter Driven) Scroll compressors, optimized for R410A in a single-circuit configuration, axial-flow fans, micro-channel full-aluminum air coils and electronic expansion valve as standard equipment.

Flexible and reliable unit; it easily adapts itself to different thermal load conditions thanks to the precise temperature control together with the use of inverter technology. The high performance's level, both full and partial load, is achieved thanks to the accurate unit's design and to the use of fixed speed motor together with variable speed (inverter) motor.

**Version**

|    |                         |
|----|-------------------------|
| -  | Basic                   |
| SL | Super-low noise version |

**Configurations**

|   |   |
|---|---|
| - | Basic function                            |
| D | Partial condensing heat recovery function |

**Features****HIGH EFFICIENCY**

Unit with high efficiency and reduced energy consumption, thanks to the inverter technology, contributing to lower operating costs and therefore achieving a quick return on investment.

**ErP READY**

The highest level of efficiency at part load, thanks to the inverter technology, can meet and exceed the minimum seasonal efficiency for cooling, SEER, according with the eco-sustainable design requirements for all products using energy. The units already comply with the minimum seasonal energy efficiency requirements that will start from 2021. For this reason, the unit represents the best choice for all the hydronic application on the residential and commercial markets. The unit is suitable also for industrial market, satisfying the seasonal energy performance ratio SEPR.

**VARIBLE PRIMARY FLOW (OPTION)**

Energy saving due to variable pump speed management based on load demand and the variable flow assures the functioning of the units also with critical working conditions.

**INTEGRATED HYDRONIC MODULE**

The built-in hydronic module already contains the main water circuit components; it is available as option with single or twin in-line pump, for achieving low or high head, fixed or variable speed and buffer tank.

**ELECTRONIC EXPANSION VALVE SUPPLIED STANDARD**

The use of the electronic expansion valve generates considerable benefits, especially in cases of variable demand and at different working conditions. It guaranteed energy saving due to efficiency optimization in various different working conditions. The electronic thermostatic valve allows you to obtain speed in reaching machine stability and an extension of the operating limits.

**ALUMINIUM MICRO-CHANNEL HEAT EXCHANGERS**

This new range of chiller uses aluminum micro-channel condensers that ensure a premium level of efficiency. This solution also allows to reduce the refrigerant charge with respect to traditional copper/aluminium coils and to reduce the weight of the unit.

**WIDE OPERATING RANGE**

Full load operation is ensured with outdoor air temperature up to 48°C during summer. Dedicated accessories allow the unit operation down to -20°C of outdoor air temperature during winter.

Production of evaporator leaving water temperature from -10°C to 20°C.

**Accessory**

- Remote control keyboard (distance to 200m and to 500m)
- Set-up for remote connectivity with ModBus/Echelon protocol cards
- Compressor power factor correction
- Soft start
- Hydronic kit available in different configurations with 1 or 2 pumps fixed speed or variable speed and buffer tank
- VPF (Variable Primary Flow) system
- EC fans with electronic DC brushless motor
- LOW NOISE KIT (only on no silenced versions)
- User Limit Control (U.L.C.) function allows a startup of the unit in all critical conditions of water and air temperature, always under the operating limits of the unit.
- Night mode is a system setting to limit maximum noise level of the unit.
- Microchannel coils with e-coating protection
- Traditional coils with copper tubes and aluminium fins, also available with prepainted fins or Fin Guard Silver protective treatment.
- Copper-Copper heat exchanger coils

**Controls****Electronic control W3000TE**

The brand new W3000TE controller offers advanced functions and algorithms. The keypad W3000 Compact, as standard equipment, features function controls and a complete LCD display for viewing data and activating the unit, via a multilevel menu, with settable display language. In addition to or as an alternative, the KIPLink is available - Keyboard In Your Pocket - is the innovative user interface based on WiFi technology that allows one to operate on the unit directly from the smartphone or tablet. Using KIPLink, it is possible to turn the unit on and off, adjust the set-point, plot the main operating variables, monitor in detail the status of the refrigerant circuits, the compressors, the fans and the pumps (if present) and display and reset the possible alarms. The regulation features the continuous modulation of capacity, based on sequential adjustment + DIP referring to the leaving water temperature (neutral zone adjustment + DIP on outlet temperature probe, for the 0151 size). Diagnostics include complete alarm management, with "blackbox" functions (via PC) and alarm log (display or PC) for best analysis of unit behaviour. The built-in clock can be used to create an operating profile containing up to 4 typical days and 10 time bands, essential for efficient programming of energy production. Optional proprietary devices can perform the adjustment of the resources in systems made of several units. Consumption metering and performance measurement are possible as well. Supervision is available with different options, using proprietary devices or by integration into third party systems using ModBus, BACnet, BACnet-over-IP and Echelon LonWorks protocols. A dedicated wall-mounted keypad can be used for remote control of all the functions. Optionally (VPF package), capacity modulation can be integrated with hydraulic flow modulation, thanks to inverter-driven pumps and to specific resources for the hydraulic circuit.





COOLING

SCROLL

P PLATES

R HFC R-410A

AXIAL

| i-NX  |        | 0151P   | 0182P | 0202P | 0262P | 0302P | 0352P | 0402P | 0502P |      |
|---|--------|---|-------|-------|-------|-------|-------|-------|-------|------|
| Power supply  |        | V/ph/Hz 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3/50 400/3/50 400/3/50 |       |       |       |       |       |       |       |      |
| <b>PERFORMANCE</b>  |        |   |       |       |       |       |       |       |       |      |
| <b>COOLING ONLY (GROSS VALUE)</b>                         |        |   |       |       |       |       |       |       |       |      |
| Cooling capacity  | (1)    | kW  | 43,9  | 52,9  | 63,1  | 72,1  | 83,8  | 101   | 120   | 129  |
| Total power input   | (1)    | kW  | 15,7  | 18,8  | 21,4  | 25,0  | 29,2  | 35,2  | 41,9  | 46,8 |
| EER   | (1)    | kW/kW   | 2,80  | 2,81  | 2,95  | 2,88  | 2,87  | 2,87  | 2,86  | 2,76 |
| ESEER   | (1)    | kW/kW   | 4,56  | 4,55  | 4,51  | 4,54  | 4,51  | 4,66  | 4,58  | 4,53 |
| <b>COOLING ONLY (EN14511 VALUE)</b>                       |        |   |       |       |       |       |       |       |       |      |
| Cooling capacity  | (1)(2) | kW  | 43,6  | 52,6  | 62,7  | 71,7  | 83,4  | 100   | 119   | 129  |
| EER   | (1)(2) | kW/kW   | 2,73  | 2,75  | 2,88  | 2,82  | 2,82  | 2,82  | 2,80  | 2,72 |
| ESEER   | (1)(2) | kW/kW   | 4,27  | 4,19  | 4,17  | 4,23  | 4,24  | 4,36  | 4,27  | 4,25 |
| Cooling energy class                                      |        |   | C     | C     | C     | C     | C     | C     | C     | C    |
| <b>ENERGY EFFICIENCY</b>                                  |        |   |       |       |       |       |       |       |       |      |
| <b>SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)</b> |        |   |       |       |       |       |       |       |       |      |
| <b>Ambient refrigeration</b>                              |        |   |       |       |       |       |       |       |       |      |
| Prated,c  | (7)    | kW  | 43,6  | 52,6  | 62,7  | 71,7  | 83,4  | 100   | 119   | 129  |
| SEER  | (7)(8) |   | 4,15  | 4,11  | 4,13  | 4,18  | 4,23  | 4,36  | 4,32  | 4,30 |
| Performance ηs  | (7)(9) | %   | 163   | 161   | 162   | 164   | 166   | 171   | 170   | 169  |
| <b>EXCHANGERS</b>   |        |   |       |       |       |       |       |       |       |      |
| <b>HEAT EXCHANGER USER SIDE IN REFRIGERATION</b>          |        |   |       |       |       |       |       |       |       |      |
| Water flow  | (1)    | l/s   | 2,10  | 2,53  | 3,02  | 3,45  | 4,01  | 4,82  | 5,73  | 6,18 |
| Pressure drop   | (1)    | kPa   | 37,2  | 41,2  | 42,3  | 39,4  | 35,0  | 36,2  | 42,9  | 38,9 |
| <b>REFRIGERANT CIRCUIT</b>                                |        |   |       |       |       |       |       |       |       |      |
| Compressors nr.   |        | N°  | 1     | 2     | 2     | 2     | 2     | 2     | 2     | 2    |
| No. Circuits  |        | N°  | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1    |
| Refrigerant charge  |        | kg  | 7,00  | 7,20  | 8,90  | 9,40  | 9,50  | 12,5  | 12,9  | 13,5 |
| <b>NOISE LEVEL</b>  |        |   |       |       |       |       |       |       |       |      |
| Sound Pressure  | (3)    | dB(A)   | 51    | 52    | 53    | 53    | 54    | 55    | 57    | 57   |
| Sound power level in cooling                              | (4)(5) | dB(A)   | 83    | 84    | 85    | 85    | 86    | 87    | 89    | 89   |
| <b>SIZE AND WEIGHT</b>                                    |        |   |       |       |       |       |       |       |       |      |
| A   | (6)    | mm  | 2000  | 2000  | 2625  | 2625  | 2625  | 3250  | 3250  | 3250 |
| B   | (6)    | mm  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350 |
| H   | (6)    | mm  | 2070  | 2070  | 2070  | 2070  | 2070  | 2170  | 2170  | 2170 |
| Operating weight  | (6)    | kg  | 600   | 660   | 750   | 780   | 810   | 1060  | 1070  | 1080 |

## Notes:

1 Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.

2 Values in compliance with EN14511-3:2013.

3 Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.

4 Sound power on the basis of measurements made in compliance with ISO 9614.

5 Sound power level in cooling, outdoors.

6 Unit in standard configuration/execution, without optional accessories.

7 Seasonal energy efficiency of the cooling environment [REGULATION (EU) N. 2016/2281]

8 Seasonal space heating energy index

9 Seasonal energy efficiency of the space cooling

The units highlighted in this publication contain HFC R410A [GWP<sub>100</sub> 2088] fluorinated greenhouse gases.

Certified data in EUROVENT

| i-NX / SL   |        | 0151P   | 0182P | 0202P | 0262P | 0302P | 0352P | 0402P | 0502P |      |
|---|--------|---|-------|-------|-------|-------|-------|-------|-------|------|
| Power supply  |        | V/ph/Hz 400/3+N/50 400/3+N/50 400/3+N/50 400/3+N/50 400/3/50 400/3/50 400/3/50 400/3/50 |       |       |       |       |       |       |       |      |
| <b>PERFORMANCE</b>  |        |   |       |       |       |       |       |       |       |      |
| <b>COOLING ONLY (GROSS VALUE)</b>                         |        |   |       |       |       |       |       |       |       |      |
| Cooling capacity  | (1)    | kW  | 42,6  | 51,2  | 60,1  | 68,1  | 81,2  | 96,7  | 115   | 124  |
| Total power input   | (1)    | kW  | 14,4  | 17,8  | 20,9  | 24,5  | 28,3  | 33,9  | 39,3  | 44,3 |
| EER   | (1)    | kW/kW   | 2,96  | 2,88  | 2,88  | 2,78  | 2,87  | 2,85  | 2,93  | 2,81 |
| ESEER   | (1)    | kW/kW   | 4,48  | 4,58  | 4,49  | 4,55  | 4,54  | 4,75  | 4,78  | 4,70 |
| <b>COOLING ONLY (EN14511 VALUE)</b>                       |        |   |       |       |       |       |       |       |       |      |
| Cooling capacity  | (1)(2) | kW  | 42,3  | 50,9  | 59,8  | 67,7  | 80,8  | 96,3  | 115   | 124  |
| EER   | (1)(2) | kW/kW   | 2,89  | 2,81  | 2,81  | 2,73  | 2,82  | 2,80  | 2,88  | 2,76 |
| ESEER   | (1)(2) | kW/kW   | 4,21  | 4,26  | 4,20  | 4,25  | 4,26  | 4,48  | 4,50  | 4,43 |
| Cooling energy class                                      |        |   | C     | C     | C     | C     | C     | C     | C     | C    |
| <b>ENERGY EFFICIENCY</b>                                  |        |   |       |       |       |       |       |       |       |      |
| <b>SEASONAL EFFICIENCY IN COOLING (Reg. EU 2016/2281)</b> |        |   |       |       |       |       |       |       |       |      |
| <b>Ambient refrigeration</b>                              |        |   |       |       |       |       |       |       |       |      |
| Prated,c  | (7)    | kW  | 42,3  | 50,9  | 59,8  | 67,7  | 80,8  | 96,3  | 115   | 124  |
| SEER  | (7)(8) |   | 4,18  | 4,10  | 4,11  | 4,17  | 4,22  | 4,46  | 4,50  | 4,48 |
| Performance $\eta_s$                                      | (7)(9) | %   | 164   | 161   | 162   | 164   | 166   | 176   | 177   | 176  |
| <b>EXCHANGERS</b>   |        |   |       |       |       |       |       |       |       |      |
| <b>HEAT EXCHANGER USER SIDE IN REFRIGERATION</b>          |        |   |       |       |       |       |       |       |       |      |
| Water flow  | (1)    | l/s   | 2,04  | 2,45  | 2,87  | 3,26  | 3,88  | 4,62  | 5,50  | 5,95 |
| Pressure drop   | (1)    | kPa   | 35,1  | 38,7  | 38,3  | 35,2  | 32,9  | 33,2  | 39,6  | 36,0 |
| <b>REFRIGERANT CIRCUIT</b>                                |        |   |       |       |       |       |       |       |       |      |
| Compressors nr.   |        | N°  | 1     | 2     | 2     | 2     | 2     | 2     | 2     | 2    |
| No. Circuits  |        | N°  | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1    |
| Refrigerant charge  |        | kg  | 8,10  | 8,30  | 8,70  | 9,20  | 11,8  | 12,3  | 14,7  | 15,2 |
| <b>NOISE LEVEL</b>  |        |   |       |       |       |       |       |       |       |      |
| Sound Pressure  | (3)    | dB(A)   | 45    | 45    | 46    | 46    | 47    | 48    | 50    | 50   |
| Sound power level in cooling                              | (4)(5) | dB(A)   | 77    | 77    | 78    | 78    | 79    | 80    | 82    | 82   |
| <b>SIZE AND WEIGHT</b>                                    |        |   |       |       |       |       |       |       |       |      |
| A   | (6)    | mm  | 2625  | 2625  | 2625  | 2625  | 3250  | 3250  | 3875  | 3875 |
| B   | (6)    | mm  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350  | 1350 |
| H   | (6)    | mm  | 2070  | 2070  | 2070  | 2070  | 2170  | 2170  | 2170  | 2170 |
| Operating weight  | (6)    | kg  | 700   | 760   | 790   | 820   | 980   | 1090  | 1180  | 1200 |

Notes:

- 1 Plant (side) cooling exchanger water (in/out) 12°C/7°C; Source (side) heat exchanger air (in) 35°C.
  - 2 Values in compliance with EN14511-3:2013.
  - 3 Average sound pressure level at 10m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.
  - 4 Sound power on the basis of measurements made in compliance with ISO 9614.
  - 5 Sound power level in cooling, outdoors.
  - 6 Unit in standard configuration/execution, without optional accessories.
  - 7 Seasonal energy efficiency of the cooling environment [REGULATION (EU) N. 2016/2281]
  - 8 Seasonal space heating energy index
  - 9 Seasonal energy efficiency of the space cooling
- The units highlighted in this publication contain HFC R410A [GWP<sub>100</sub> 2088] fluorinated greenhouse gases.
- Certified data in EUROVENT

